

Programming with ZooKeeper - A basic tutorial

by

Table of contents

1 Introduction.....	2
2 Barriers.....	3
3 Producer-Consumer Queues.....	5
4 Complete example.....	7
4.1 Queue test.....	7
4.2 Barrier test.....	8
4.3 Source Listing.....	8

1 Introduction

In this tutorial, we show simple implementations of barriers and producer-consumer queues using ZooKeeper. We call the respective classes Barrier and Queue. These examples assume that you have at least one ZooKeeper server running.

Both primitives use the following common excerpt of code:

```
static ZooKeeper zk = null;
static Integer mutex;

String root;

SyncPrimitive(String address) {
    if(zk == null){
        try {
            System.out.println("Starting ZK:");
            zk = new ZooKeeper(address, 3000, this);
            mutex = new Integer(-1);
            System.out.println("Finished starting ZK: " + zk);
        } catch (IOException e) {
            System.out.println(e.toString());
            zk = null;
        }
    }
}

synchronized public void process(WatchedEvent event) {
    synchronized (mutex) {
        mutex.notify();
    }
}
```

Both classes extend SyncPrimitive. In this way, we execute steps that are common to all primitives in the constructor of SyncPrimitive. To keep the examples simple, we create a ZooKeeper object the first time we instantiate either a barrier object or a queue object, and we declare a static variable that is a reference to this object. The subsequent instances of Barrier and Queue check whether a ZooKeeper object exists. Alternatively, we could have the application creating a ZooKeeper object and passing it to the constructor of Barrier and Queue.

We use the process() method to process notifications triggered due to watches. In the following discussion, we present code that sets watches. A watch is internal structure that enables ZooKeeper to notify a client of a change to a node. For example, if a client is waiting for other clients to leave a barrier, then it can set a watch and wait for modifications to a particular node, which can indicate that it is the end of the wait. This point becomes clear once we go over the examples.

2 Barriers

A barrier is a primitive that enables a group of processes to synchronize the beginning and the end of a computation. The general idea of this implementation is to have a barrier node that serves the purpose of being a parent for individual process nodes. Suppose that we call the barrier node `/b1`. Each process `"p"` then creates a node `/b1/p`. Once enough processes have created their corresponding nodes, joined processes can start the computation.

In this example, each process instantiates a Barrier object, and its constructor takes as parameters:

- the address of a ZooKeeper server (e.g., `"zoo1.foo.com:2181"`)
- the path of the barrier node on ZooKeeper (e.g., `/b1`)
- the size of the group of processes

The constructor of Barrier passes the address of the Zookeeper server to the constructor of the parent class. The parent class creates a ZooKeeper instance if one does not exist. The constructor of Barrier then creates a barrier node on ZooKeeper, which is the parent node of all process nodes, and we call root (**Note:** This is not the ZooKeeper root `"/`).

```

/**
 * Barrier constructor
 *
 * @param address
 * @param root
 * @param size
 */
Barrier(String address, String root, int size) {
    super(address);
    this.root = root;
    this.size = size;

    // Create barrier node
    if (zk != null) {
        try {
            Stat s = zk.exists(root, false);
            if (s == null) {
                zk.create(root, new byte[0], Ids.OPEN_ACL_UNSAFE,
                    CreateMode.PERSISTENT);
            }
        } catch (KeeperException e) {
            System.out
                .println("Keeper exception when instantiating queue: "
                    + e.toString());
        } catch (InterruptedException e) {
            System.out.println("Interrupted exception");
        }
    }

    // My node name
    try {
        name = new
String(InetAddress.getLocalHost().getCanonicalHostName().toString());

```

```

    } catch (UnknownHostException e) {
        System.out.println(e.toString());
    }
}

```

To enter the barrier, a process calls `enter()`. The process creates a node under the root to represent it, using its host name to form the node name. It then wait until enough processes have entered the barrier. A process does it by checking the number of children the root node has with `getChildren()`, and waiting for notifications in the case it does not have enough. To receive a notification when there is a change to the root node, a process has to set a watch, and does it through the call to `getChildren()`. In the code, we have that `getChildren()` has two parameters. The first one states the node to read from, and the second is a boolean flag that enables the process to set a watch. In the code the flag is true.

```

/**
 * Join barrier
 *
 * @return
 * @throws KeeperException
 * @throws InterruptedException
 */
boolean enter() throws KeeperException, InterruptedException{
    zk.create(root + "/" + name, new byte[0], Ids.OPEN_ACL_UNSAFE,
        CreateMode.EPHEMERAL_SEQUENTIAL);
    while (true) {
        synchronized (mutex) {
            List<String> list = zk.getChildren(root, true);

            if (list.size() < size) {
                mutex.wait();
            } else {
                return true;
            }
        }
    }
}

```

Note that `enter()` throws both `KeeperException` and `InterruptedException`, so it is the responsibility of the application to catch and handle such exceptions.

Once the computation is finished, a process calls `leave()` to leave the barrier. First it deletes its corresponding node, and then it gets the children of the root node. If there is at least one child, then it waits for a notification (obs: note that the second parameter of the call to `getChildren()` is true, meaning that ZooKeeper has to set a watch on the the root node). Upon reception of a notification, it checks once more whether the root node has any child.

```

/**
 * Wait until all reach barrier

```



```

        System.out
            .println("Keeper exception when instantiating queue: "
                + e.toString());
    } catch (InterruptedException e) {
        System.out.println("Interrupted exception");
    }
}

```

A producer process calls "produce()" to add an element to the queue, and passes an integer as an argument. To add an element to the queue, the method creates a new node using "create()", and uses the SEQUENCE flag to instruct ZooKeeper to append the value of the sequencer counter associated to the root node. In this way, we impose a total order on the elements of the queue, thus guaranteeing that the oldest element of the queue is the next one consumed.

```

/**
 * Add element to the queue.
 *
 * @param i
 * @return
 */
boolean produce(int i) throws KeeperException, InterruptedException{
    ByteBuffer b = ByteBuffer.allocate(4);
    byte[] value;

    // Add child with value i
    b.putInt(i);
    value = b.array();
    zk.create(root + "/element", value, Ids.OPEN_ACL_UNSAFE,
        CreateMode.PERSISTENT_SEQUENTIAL);

    return true;
}

```

To consume an element, a consumer process obtains the children of the root node, reads the node with smallest counter value, and returns the element. Note that if there is a conflict, then one of the two contending processes won't be able to delete the node and the delete operation will throw an exception.

A call to getChildren() returns the list of children in lexicographic order. As lexicographic order does not necessary follow the numerical order of the counter values, we need to decide which element is the smallest. To decide which one has the smallest counter value, we traverse the list, and remove the prefix "element" from each one.

```

/**
 * Remove first element from the queue.
 *
 * @return
 * @throws KeeperException

```

```

    * @throws InterruptedException
    */
    int consume() throws KeeperException, InterruptedException{
        int retvalue = -1;
        Stat stat = null;

        // Get the first element available
        while (true) {
            synchronized (mutex) {
                List<String> list = zk.getChildren(root, true);
                if (list.size() == 0) {
                    System.out.println("Going to wait");
                    mutex.wait();
                } else {
                    Integer min = new Integer(list.get(0).substring(7));
                    for(String s : list){
                        Integer tempValue = new Integer(s.substring(7));
                        //System.out.println("Temporary value: " + tempValue);
                        if(tempValue < min) min = tempValue;
                    }
                    System.out.println("Temporary value: " + root + "/" + element + min);
                    byte[] b = zk.getData(root + "/" + element + min,
                        false, stat);
                    zk.delete(root + "/" + element + min, 0);
                    ByteBuffer buffer = ByteBuffer.wrap(b);
                    retvalue = buffer.getInt();

                    return retvalue;
                }
            }
        }
    }
}

```

4 Complete example

In the following section you can find a complete command line application to demonstrate the above mentioned recipes. Use the following command to run it.

```

ZOOBINDIR="[path_to_distro]/bin"
. "$ZOOBINDIR"/zkEnv.sh
java SyncPrimitive [Test Type] [ZK server] [No of elements] [Client type]

```

4.1 Queue test

Start a producer to create 100 elements

```
java SyncPrimitive qTest localhost 100 p
```

Start a consumer to consume 100 elements

```
java SyncPrimitive qTest localhost 100 c
```

4.2 Barrier test

Start a barrier with 2 participants (start as many times as many participants you'd like to enter)

```
java SyncPrimitive bTest localhost 2
```

4.3 Source Listing

SyncPrimitive.JavaSyncPrimitive.Java

```
import java.io.IOException;
import java.net.InetAddress;
import java.net.UnknownHostException;
import java.nio.ByteBuffer;
import java.util.List;
import java.util.Random;

import org.apache.zookeeper.CreateMode;
import org.apache.zookeeper.KeeperException;
import org.apache.zookeeper.WatchedEvent;
import org.apache.zookeeper.Watcher;
import org.apache.zookeeper.ZooKeeper;
import org.apache.zookeeper.ZooDefs.Ids;
import org.apache.zookeeper.data.Stat;

public class SyncPrimitive implements Watcher {

    static ZooKeeper zk = null;
    static Integer mutex;

    String root;

    SyncPrimitive(String address) {
        if(zk == null){
            try {
                System.out.println("Starting ZK:");
                zk = new ZooKeeper(address, 3000, this);
                mutex = new Integer(-1);
                System.out.println("Finished starting ZK: " + zk);
            } catch (IOException e) {
                System.out.println(e.toString());
                zk = null;
            }
        }
        //else mutex = new Integer(-1);
    }

    synchronized public void process(WatchedEvent event) {
        synchronized (mutex) {
            //System.out.println("Process: " + event.getType());
            mutex.notify();
        }
    }
}
```

```

    }
}

/**
 * Barrier
 */
static public class Barrier extends SyncPrimitive {
    int size;
    String name;

    /**
     * Barrier constructor
     *
     * @param address
     * @param root
     * @param size
     */
    Barrier(String address, String root, int size) {
        super(address);
        this.root = root;
        this.size = size;

        // Create barrier node
        if (zk != null) {
            try {
                Stat s = zk.exists(root, false);
                if (s == null) {
                    zk.create(root, new byte[0], Ids.OPEN_ACL_UNSAFE,
                        CreateMode.PERSISTENT);
                }
            } catch (KeeperException e) {
                System.out
                    .println("Keeper exception when instantiating queue: "
                        + e.toString());
            } catch (InterruptedException e) {
                System.out.println("Interrupted exception");
            }
        }

        // My node name
        try {
            name = new
                String(InetAddress.getLocalHost().getCanonicalHostName().toString());
        } catch (UnknownHostException e) {
            System.out.println(e.toString());
        }
    }

    /**
     * Join barrier
     *
     * @return
     * @throws KeeperException
     * @throws InterruptedException
     */
    boolean enter() throws KeeperException, InterruptedException {
        zk.create(root + "/" + name, new byte[0], Ids.OPEN_ACL_UNSAFE,
            CreateMode.EPHEMERAL_SEQUENTIAL);
    }
}

```

```

        while (true) {
            synchronized (mutex) {
                List<String> list = zk.getChildren(root, true);

                if (list.size() < size) {
                    mutex.wait();
                } else {
                    return true;
                }
            }
        }
    }

    /**
     * Wait until all reach barrier
     *
     * @return
     * @throws KeeperException
     * @throws InterruptedException
     */

    boolean leave() throws KeeperException, InterruptedException {
        zk.delete(root + "/" + name, 0);
        while (true) {
            synchronized (mutex) {
                List<String> list = zk.getChildren(root, true);
                if (list.size() > 0) {
                    mutex.wait();
                } else {
                    return true;
                }
            }
        }
    }

    /**
     * Producer-Consumer queue
     */
    static public class Queue extends SyncPrimitive {

        /**
         * Constructor of producer-consumer queue
         *
         * @param address
         * @param name
         */
        Queue(String address, String name) {
            super(address);
            this.root = name;
            // Create ZK node name
            if (zk != null) {
                try {
                    Stat s = zk.exists(root, false);
                    if (s == null) {
                        zk.create(root, new byte[0], Ids.OPEN_ACL_UNSAFE,
                                CreateMode.PERSISTENT);
                    }
                } catch (KeeperException e) {
                    System.out

```

```

        .println("Keeper exception when instantiating queue: "
            + e.toString());
    } catch (InterruptedException e) {
        System.out.println("InterruptedException");
    }
}

/**
 * Add element to the queue.
 *
 * @param i
 * @return
 */
boolean produce(int i) throws KeeperException, InterruptedException{
    ByteBuffer b = ByteBuffer.allocate(4);
    byte[] value;

    // Add child with value i
    b.putInt(i);
    value = b.array();
    zk.create(root + "/element", value, Ids.OPEN_ACL_UNSAFE,
        CreateMode.PERSISTENT_SEQUENTIAL);

    return true;
}

/**
 * Remove first element from the queue.
 *
 * @return
 * @throws KeeperException
 * @throws InterruptedException
 */
int consume() throws KeeperException, InterruptedException{
    int retvalue = -1;
    Stat stat = null;

    // Get the first element available
    while (true) {
        synchronized (mutex) {
            List<String> list = zk.getChildren(root, true);
            if (list.size() == 0) {
                System.out.println("Going to wait");
                mutex.wait();
            } else {
                Integer min = new Integer(list.get(0).substring(7));
                String minNode = list.get(0);
                for(String s : list){
                    Integer tempValue = new Integer(s.substring(7));
                    //System.out.println("Temporary value: " + tempValue);
                    if(tempValue < min) {
                        min = tempValue;
                        minNode = s;
                    }
                }
                System.out.println("Temporary value: " + root + "/" +
minNode);

```

```

        byte[] b = zk.getData(root + "/" + minNode,
            false, stat);
        zk.delete(root + "/" + minNode, 0);
        ByteBuffer buffer = ByteBuffer.wrap(b);
        retvalue = buffer.getInt();

        return retvalue;
    }
}

public static void main(String args[]) {
    if (args[0].equals("qTest"))
        queueTest(args);
    else
        barrierTest(args);
}

public static void queueTest(String args[]) {
    Queue q = new Queue(args[1], "/appl");

    System.out.println("Input: " + args[1]);
    int i;
    Integer max = new Integer(args[2]);

    if (args[3].equals("p")) {
        System.out.println("Producer");
        for (i = 0; i < max; i++)
            try{
                q.produce(10 + i);
            } catch (KeeperException e){
            } catch (InterruptedException e){
            }
    } else {
        System.out.println("Consumer");

        for (i = 0; i < max; i++) {
            try{
                int r = q.consume();
                System.out.println("Item: " + r);
            } catch (KeeperException e){
                i--;
            } catch (InterruptedException e){
            }
        }
    }
}

public static void barrierTest(String args[]) {
    Barrier b = new Barrier(args[1], "/b1", new Integer(args[2]));
    try{
        boolean flag = b.enter();
        System.out.println("Entered barrier: " + args[2]);
        if(!flag) System.out.println("Error when entering the barrier");
    }
}

```

```
    } catch (KeeperException e){
    } catch (InterruptedException e){
    }

    // Generate random integer
    Random rand = new Random();
    int r = rand.nextInt(100);
    // Loop for rand iterations
    for (int i = 0; i < r; i++) {
        try {
            Thread.sleep(100);
        } catch (InterruptedException e) {
        }
    }
    try{
        b.leave();
    } catch (KeeperException e){
    } catch (InterruptedException e){
    }
    System.out.println("Left barrier");
}
}
```